



## Specifications Multipack 15x Bright Choice LED Downlight UltraSlim 24W 1950lm 110D - 840 Cool White | 295mm - Cutout 280mm

[View Product](#)

### General Information

|                          |                                                                                                 |
|--------------------------|-------------------------------------------------------------------------------------------------|
| SKU                      | 248643                                                                                          |
| EAN                      | 8719157048026                                                                                   |
| Manufacturer Code        | 8719157048026                                                                                   |
| Brand                    | Non-branded                                                                                     |
| Manufacturer Name        | Multipack 15x White label LED Downlight Round UltraSlim 24W 1950lm 840 CutoutØ280mm FrameØ295mm |
| Any Lamp all-in warranty | 2 Years                                                                                         |
| Average Lifetime (h)     | 20000                                                                                           |

### Technical Information

|                             |                   |
|-----------------------------|-------------------|
| Emergency Lighting          | No Emergency Unit |
| Tiltable                    | No                |
| Technology                  | LED Integrated    |
| Replaces (Watt)             | 50                |
| Wattage                     | 24W               |
| Voltage (V)                 | 220-240           |
| Dimmable                    | Not Dimmable      |
| Colour Code                 | 840 Cool White    |
| Colour temperature (Kelvin) | 4000 Cool White   |
| Colour Rendering (Ra)       | 80-89             |
| Colour of Light             | White             |

|                          |                          |
|--------------------------|--------------------------|
| Light colour options     | Single Color             |
| Beam Angle (degree)      | 110                      |
| Luminous Flux (Lumen)    | 1950lm                   |
| Luminous Efficacy (lm/W) | 80                       |
| Power factor             | >0.70                    |
| Unified Glare Rating     | < 22 - for general areas |
| Product Type Category    | LED Downlight            |

## Fixture Information

|                        |                   |
|------------------------|-------------------|
| Mounting Method        | Recessed          |
| Cut out (mm)           | 280               |
| IP-rating              | IP20              |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature  | -20 to +40        |
| Colour of the Fixture  | White             |
| Colour of material     | White             |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 11  |
| Diameter (mm) | 300 |

## Sensor Information

Type of sensor

**Why Any-lamp?**  
No Sensor



Order from the **largest lighting specialist** in Europe



**Customised** quotation



Up to **7 years warranty**



**Easy** return process